

#### TeraResist 8000 ME - Case set with 2 electrodes

**Product Number** EP0201074



## **Product Description**

## TeraResist 8000 ME high ohmmeter

The TERA-RESIST 8000 ME is a high-resistance ohmmeter for **measuring surface resistance**. It is operated via a **color touch display**. The high-ohmmeter offers **four fixed measuring voltages**: 10 V, 100 V, 500 V and 1000 V.

The auto measuring voltage function switches the measuring voltage automatically.

The timer function allows you to measure over a defined period of time.

An internal memory stores all measured values, which you can send to the PC via the USB interface using data export.

The **supplied software** imports and visualizes your measured values. The TERA-RESIST 8000 ME ohmmeter is supplied **with two measuring electrodes**, two silicone measuring leads and a power supply unit in a sturdy aluminum case.

- Tera ohmmeter with touch screen display in case set
- Operation via color touch screen display
- 4 fixed measuring voltages
  - 10 V, for measurements from 1 K\( to 200 G\( \),
  - 100 V, for measurements from 100 K\( to 2 T\( Z \);
  - 500 V, for measurements from 500 K\( to 5 T\( \);
  - 1,000 V, for measurements from 1 M\( \text{to 10 T\( \text{M} \)};

ESD-PROTECT GmbH | +49 2689 92870-0 | info@esd-protect.de



- Measurement of humidity and temperature
- Auto measuring voltage (automatic switching of the measuring voltage)
- Timer function (measurements over a definable period of time)
- Break-down resistance measurement with graphical display
- Internal memory for measured values with additional transfer of temperature, humidity, date and time
- USB interface for data export and PC display (via supplied software)

#### Scope of delivery:

- Tera ohmmeter TeraResist 8000
- Plug-in power supply 230V~ / 50Hz 9V DC / 300mA
- 4 x AA Mignon NiMH batteries
- Test lead (yellow) 2m, safety plug to safety plug (4 mm), touch-proof
- Measuring lead (red) 3m, safety plug to safety plug (4 mm), touch-proof
- 2 measuring electrodes 2.5 kg according to EOS/ESD-S4.1 and S7.1
- USB cable
- PC software KL\_ReadOut on USB stick
- Operating instructions
- Calibration certificate
- Sturdy ALU case

Also available as a PRORENT rental device.

ESD-PROTECT GmbH | +49 2689 92870-0 | info@esd-protect.de

# **More Images**





