

ESD-ProFloor PF 50 earth connection tile

Product Number EP0502053



Product Description

The ESD-ProFloor PF 50 ground connection tile is a very versatile flooring system with high quality and outstanding properties. Its easy installation thanks to interlocking joints with click-and-use installation ensures quick and easy installation. This ground connection tile complies with ISO90001, ISO 61340/5, EN 1081, EN 1815 & EN6356, EC 19072006 and is suitable for use with trolleys and pallet trucks up to 600 kg. Class Bfl s1 fire resistance ensures good fire protection.

- incl. DK 10 mm connection and 2 meters of carbon fibre tape
- Dimensions: 503 x 503 x 5 mm
- Surface resistance 10 ⁴ Ohm to 10 ⁶ Ohm
- Leakage resistance 10 ⁴ Ohm to 10 ⁶ Ohm
- Homogeneous resistances over the entire surface
- Dimensionally stable
- Color: dark grey
- Suitable for use with transport trolleys and pallet trucks up to 600 kg
- complies with the standards ISO90001, ISO 61340/5, EN 1081, EN 1815 & EN6356, EC 19072006
- Shore A: 92, DIN 53516: 17 N/mm2
- easy installation thanks to interlocking joints
- Click-and-use installation
- chemical-resistant, reduces dust and noise, slip-resistant
- Insulation of the floor against cold and moisture
- fire-retardant class Bfl s1
- re-layable
- Price per tile

ESD-PROTECT GmbH | +49 2689 92870-0 | info@esd-protect.de