

SCS EM EYE-Meter Multifunctional measuring device 770715

Product Number EP0201100



Product Description

Multifunction measuring device EM Eye Meter incl. ESD sensor

The EYE meter **detects**, **counts and measures ESD events** that can cause faults in other components. The device calculates the event size for the Charged Device Model (CDM), the Human Body Model (HBM) and the Machine Model (MM).

All measurements are recorded on a micro SD card and can therefore be downloaded to any PC for further processing or archiving. The EYE-Meter is easy and intuitive to operate via a touchscreen display. With additional optional attachments (sensors), the EYE-Meter becomes a portable detector for recording ESD events (discharges) and electromagnetic fields.



• ESD event meter

Detects, counts and measures ESD events that can damage ESD objects and lead to tool blockages, irregular behavior and parametric errors

• Power slide switch

Saves power from the rechargeable lithium-ion battery during storage

• Selectable ESD event models

Calculates the event size for the Charged Device Model (CDM), the Human Body Model (HBM) and the Machine Model (MM)

• microSD card memory

Records all measurements for PC download

• Touchscreen display

Offers an intuitive user interface

Scope of delivery:

- EM EYE Meter multifunction measuring device
- ESD sensor EP0201035
- MicroSD card, 4GB
- Power adapter, 5VDC
- incl. CTC113 remote antenna
- RF cable
- sturdy aluminum case
- Calibration certificate

ESD-PROTECT GmbH | +49 2689 92870-0 | info@esd-protect.de



Audio indicators Speaker: beep or analog audio with volume control

Recording interval Peaks: 1-360 seconds

Averages: 0.1-360 seconds

Display Touchscreen monitor 32 x 105 mm, 65W

External memory microSD card

Headphone connection 3.5mm jack plug

Charger 240V, 50-60 Hz, 0.2A

ESD event sensor

Input resolution lmV (lmV-15mV); 15 mV (15mV-1500mV)

Range detection 1.3cm - 38.1cm

EM Fields Sensor

Calibration frequency 1 GHz

Antenna factor -40.0 to 40 dBm

RF signals Sensor

Dynamic range Min: -55 dBm

Max: 0 dBm

Attenuation 00 dB / 20 dB

Also available as a PRORENT rental device.

More Images













