

ESD pendant light TANEO STZL with LED, 5000K

Product Number EP0804011



Product Description

Waldmann ESD luminaires are designed to prevent electrostatic charging and enable controlled dissipation of voltages. This is achieved using special materials and coatings.

The flat, homogeneous light with soft transitions relieves strain on the eyes during demanding visual tasks. The balanced, easily adjustable frame ensures greater comfort.

Special:

- Ideal in production, assembly and laboratories
- Shadow-free and glare-free surface light
- Good contrast vision
- very good color rendering thanks to premium LEDs

Technical data:

LED control gear Electronic transformer Connected loads 100 – 240 V; AC; 50 Hz; 60 Hz Secondary voltage 24 V Power consumption approx. 23 W Secondary power consumption approx. 19 W Luminous flux approx. 1,350 lm Luminous efficacy 1) approx. 71 lm/W Light type/color neutral white Colour temperature approx. 4,900 K Colour rendering $R_a \geq 90$; $R_9 \geq 50$ Light distribution direct Direct component approx. 100 % Beam angle 75° Colour tolerance 4 SDCM Max. Luminance (L_{65}) $\leq 12,000 \text{ cd/m}^2$ UGR class (4H 8H) ≤ 25 Protection class IP 20 Protection class I with plug-in power supply unit, III without plug-in power supply unit Technology Touch DIM switch Multi-function push-button Housing black Textured illuminant cover; plastic rods black Hinges Spring Weight approx. 1.9 kg Mains cable approx. 3.4 m; mains plug; CEE 7/VII fixing spigot16; table clamp (accessory); base

Special features ESD version

More Images

